



Mini 3 LED Module



Game Player Mini Series is designed for Small and medium channel letters. Invented cable hiding technology allows installer to hide cable beneath the module without any additional cable holder, or silicon. Therefore installer can easily adjust the gap in between modules via this technic. Midi Series can easily compatible with Profiles snap in technology. So there is no need to tape it, screw it or glue it. Snap it and go!

It features an advanced optic technologies at small footprint. Each optics have got bigger than 160° wide angle and expands its coverage across the sign demanding fewer modules per sign than standard market products.

Features

- ✓ Channel letters and box signs
7.5 cm - 12.5 cm | 75mm - 125mm
- ✓ Cable Hiding Technology (Patent Pending)
- ✓ Efficient Circuit Design (Patent Pending)
- ✓ Clean White Technology
- ✓ Snap-in compatible to TMT LEDs
Aluminum Profiles (Patent Pending)
- ✓ 3 Steps to Mac Adam Ellipse

Applications

- ✓ Ideal Channel Letters
5 cm - 15 cm | 50mm -150mm >120lm/W





TMT Elektronik Sistemleri
Sanayi A.Ş.
info@tmtleds.com
www.tmtleds.com

Datasheet Game Player TDS-Mini 3



Operating Temperature	-30°C~ +60°C	Lead Wire	Tin Coated Copper Wire
Storage Temperature	-30°C~ +60°C	Lifetime TM21	>60.000 Hours
Body Material	Case: ABS Optics: Optical PC	Adhesive Tape	3M Foam
Finishing	Ultrasonic Welding	Strip Size	50 Modules/Strip

CONSTANT VOLTAGE | 12V DC | 5 SDCM | 160° BEAM ANGLE

	Mini 3	Mini 3 HO	Mini 3 HO MAX
Power	0.48W	0.72W	1W
Current	40 mA	60 mA	83 mA
Modules Per Meter	4.9	4.9	4.9
60W PS Load	110 Total / 75 Single	75 Total / 25 Single	55 Total / 25 Single
Color	Order Code Lumens Lm/W	Order Code Lumens Lm/W	Order Code Lumens Lm/W
6.500K	105697 65 135	105698 85 118	105699 104 104

Packaging Details Chain Bag Box
50 pcs 100 pcs 1.000 pcs

Can Depth (cm) ■ Optimal ■ Acceptable

Density Guideline	1"	2"	3"	4"	5"	6"	7"	8"	9"	10+"
MINI 3	■	■	■	■	■					
MINI 3 HO		■	■	■	■	■	■	■	■	■
MINI 3 HO MAX			■	■	■	■	■	■	■	■

Luminous flux tolerance ±10% - CCT tolerance ±8%

